



PRODUCT DATA SHEET

Product Category	Product Name	Grade
POPOLYMER	POLYPOLYETHYLENE - LDPE	2100TN00

PROPERTY	Test Method	Unit	Value
MFI (200 o c/5kg)	ISO 1133	g/10 min	0.3
Density	ISO 1183 (A)	Kg/m3	921
Haze	ASTM D 1003 (A)	%	15
Clarity	DSM Method	mV	56
Gloss	ASTM D2457	%	39±5
Anti Oxidant	DSM Method	ppm	600±60
Anti Block	-	ppm	-
Slip	-	ppm	-
Impact Strength	ASTM D4272	kJ/m	35
Tear strength TD	ISO 6383-2	KN/m	25
Tear strength MD	ISO 6383-2	KN/m	20
Yield Stress TD	ISO R527-1	MPa	11
Yield Stress MD	ISO R527-1	MPa	12
Tensile strength TD	ISO R527-1	MPa	26
Tensile strength MD	ISO R527-1	MPa	29
Elongation @ break TD	ISO R527-1	%	>500
Elongation @ break MD	ISO R527-1	%	>200
Modulus of elasticity TD	ISO R527-1	MPa	190
Modulus of elasticity MD	ISO R527-1	MPa	180
Co efficient of friction	ASTM D1894	-	0.7

Application: It is suitable for application in Shrink hoods, Industrial sacks, Heavy duty, carrier bags and liners.

Packaging: 25 Kg plastic bag

ADDRESS AND CONTACT DETAIL.....