



## PRODUCT DATA SHEET

Product Category	Product Name	Grade
Oil & Gas	Gas Oil	Gas Oil

Analysis	Unit	Limit	Test Method
Density @ 15 DC	Kg/m3	820-860	ASTM D1298
Distillation:			
Recovered @ 150 DC Recovered @ 300 DC Recovered @ 375 DC	Vol% Vol% Vol%	Report Report 90 min	ASTM D86 ASTM D86 ASTM D86
F.B.P	DC	385 max	ASTM D86
Colour		3 max	ASTM D1500
Flash Point	DC	54 min	ASTM D93
Sulphur Total	wt%	1 max	ASTM D1552
Corrosion-3hrs @100 DC		1 a	ASTM D130
Viscosity Kinematic @ 37.8 DC	c.St	2.0-2.5	ASTM D445
Cloud Point	DC	2.0 max	ASTM D2500
Pour Point	DC	-3.0 max	ASTM D97
Carbon Residue (on 10 % bottoms)	wt%	0.1 max	ASTM D189
Ash	wt%	0.01 max	ASTM D482
Water & Sediment	Vol%	0.05 max	ASTM D2709
Centane Index		50 min	ASTM D976

**Application:** Fuel for Diesel engine cars and vessels

**Packaging:** Bulk